

	DECLARATION OF PERFORMANCE According to Construction Product Regulation n° 305/2011
	DoP N°15/0559

1. Unique identification code of the product-type:
BCR HYBRID

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
BCR + content in ml + HYBRID. Example BCR 400 HYBRID

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
--

Generic type and use	Bonded anchor for anchorage of threaded rod.							
Size covered	M8	M10	M12	M14	M16	M20	M24	
hef [mm]	min	60	70	80	80	100	120	145
	max	160	200	240	280	320	400	480

Generic type and use	Bonded anchor for anchorage of rebars with improved adhesion				
Size covered	Ø8	Ø10	Ø12	Ø14	Ø16
hef [mm]	min	60	70	80	100
	max	160	200	240	280

Base material and strength class	Reinforced or unreinforced normal weight concrete of strength class C20/25 at minimum to C50/60 at maximum according to EN 206-1.
---	---

Base material condition	Non cracked from M8 a M24 and from Ø8 a Ø16, cracked from M10 to M16. Seismic category C1 for M12 and M16 e Seismic category C2 for M12.
--------------------------------	---

Anchor metal material and corresponding environmental exposure	Threaded rod:
	X1) Structures subject to dry internal conditions: elements made of galvanized steel (galvanized or hot galvanized) and stainless steel A2, A4 or high corrosion resistance steel (HCR).
	X2) Structures subject to external atmospheric exposure (including industrial and marine environment) and permanently wet internal conditions, if there are no particular aggressive conditions: Elements made of A4 stainless steel or high corrosion resistance steel (HCR).
	X3) Structures subject to external atmospheric exposure (including industrial and marine environment) and to permanently wet internal conditions, if other particular aggressive conditions exist. Such particularly aggressive conditions are eg. permanent immersion, alternating in sea water or in the sea water spray area, chloride atmosphere of swimming pools or indoor environments with chemical pollution (eg in desulphurisation plants or road tunnels where de-icing materials are used): Elements made of corrosion-resistant steel (HCR)
	Bars with improved adhesion class B or C according to EN 1992-1-1.

Type of loading	Static or quasi-static loading and seismic category C1 and C2.
Service temperature range	a) from -40°C to +40°C (max. short term temperature +40°C and max. long term temperature +24°C). b) from -40°C to +50°C (max. short term temperature +50°C and max. long term temperature +40°C).
Use category	Category 1 and 2: dry and wet concrete and flooded hole (flooded hole only for threaded rod). Overhead installation is allowed. Perforation with hammer drilling machine

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Bossong S.p.A. - via Enrico Fermi 49/51 - 24050 Grassobbio (Bg) – Italy – www.bossong.com

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):
Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:
Not applicable

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued
ETA-Danmark issued 'ETA-15/0559 on the basis of EAD 330499-01-0601
TZUS (n°1020) performed:
the determination of the product type on the basis of type testing (including sampling), type calculation, tabulated values or descriptive documentation of the product; the initial inspection of the factory and of the factory production control; the continuous surveillance; assessment and approval of the factory production control; under system 1 and issue the certificate of conformity n° 1020-CPR-090-043724.

9. Declared performance:

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601							
ESSENTIAL CHARACTERISTICS	PERFORMANCE ACCORDING TO ETA-15/0559						
Installation parameters	M8	M10	M12	M14	M16	M20	M24
d [mm]	8	10	12	14	16	20	24
d ₀ [mm]	10	12	14	16	18	24	28
d _{fix} [mm]	9	12	14	16	18	22	26
h ₁ [mm]	h _{ef} + 5 mm						
h _{min} [mm]	MAX { h _{ef} + 30 mm; ≥ 100 mm; h _{ef} + 2d ₀ }						
T _{inst} [Nm]	10	20	40	40	80	130	200
S _{min} [mm]	40	50	60	75	75	90	115
C _{min} [mm]	40	40	40	50	50	55	60
γ _{inst} [-]Category I1	1,20						
γ _{inst} [-]Category I2	1,40						
Resistance for tensile load	M8	M10	M12	M14	M16	M20	M24
Characteristic steel resistance	M8	M10	M12	M14	M16	M20	M24
Steel class 4.8 N _{Rk,s} [kN]	15	23	34	46	63	98	141
Steel class 5.8 N _{Rk,s} [kN]	18	29	42	58	78	122	176
Steel class 8.8 N _{Rk,s} [kN]	29	46	67	92	126	196	282
Stainless steel A2, A4, HCR class 50 N _{Rk,s} [kN]	18	29	42	58	78	122	176
Stainless steel A2, A4, HCR class 70 N _{Rk,s} [kN]	26	41	59	81	110	171	247
Stainless steel A4, HCR class 80 N _{Rk,s} [kN]	29	46	67	92	126	196	282

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601								
ESSENTIAL CHARACTERISTICS		PERFORMANCE ACCORDING TO ETA-15/0559						
Resistance for shear load Characteristic steel resistance without lever arm		M8	M10	M12	M14	M16	M20	M24
Steel class 4.8 $V_{Rk,s}^0$ [kN]		7	12	17	23	31	49	71
Steel class 5.8 $V_{Rk,s}^0$ [kN]		9	14	21	29	39	61	88
Steel class 8.8 $V_{Rk,s}^0$ [kN]		15	23	34	46	63	98	141
Stainless steel A2, A4, HCR class 50 $V_{Rk,s}^0$ [kN]		9	14	21	29	39	61	88
Stainless steel A2, A4, HCR class 70 $V_{Rk,s}^0$ [kN]		13	20	29	40	55	86	124
Stainless steel A4, HCR class 80 $V_{Rk,s}^0$ [kN]		15	23	34	46	63	98	141
k_7		1,0						
Resistance for shear load Characteristic steel resistance with lever arm		M8	M10	M12	M14	M16	M20	M24
Steel class 4.8 $M_{Rk,s}^0$ [Nm]		15	30	52	83	133	260	449
Steel class 5.8 $M_{Rk,s}^0$ [Nm]		19	37	66	104	166	324	561
Steel class 8.8 $M_{Rk,s}^0$ [Nm]		30	60	105	167	266	519	898
Stainless steel A2, A4, HCR class 50 $M_{Rk,s}^0$ [Nm]		19	37	66	104	166	324	561
Stainless steel A2, A4, HCR class 70 $M_{Rk,s}^0$ [Nm]		26	52	92	146	233	454	786
Stainless steel A4, HCR class 80 $M_{Rk,s}^0$ [Nm]		30	60	105	167	266	519	898
Resistance for tensile load Characteristic resistance for combined pullout and concrete cone failure		M8	M10	M12	M14	M16	M20	M24
$\tau_{Rk,ucr}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+40°C ($T_{mlp} = 24^\circ\text{C}$)		13,0	13,0	12,0	12,0	10,0	9,5	9,0
$\tau_{Rk,ucr}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+50°C ($T_{mlp} = 40^\circ\text{C}$)		13,0	12,0	11,0	11,0	9,5	9,0	8,0
$\tau_{Rk,cr}$ [N/mm ²] cracked concrete C20/25 Temperature range -40°C/+40°C ($T_{mlp} = 24^\circ\text{C}$)		-	4,0	5,0	5,0	5,0	-	-
$\tau_{Rk,cr}$ [N/mm ²] cracked concrete C20/25 Temperature range -40°C/+50°C ($T_{mlp} = 40^\circ\text{C}$)		-	4,0	5,0	5,0	5,0	-	-
$\psi_{c,ucr/cr}$ [-]		1,00						
ψ_{sus}^0 Temperature range -40°C/+40°C		0,68						
ψ_{sus}^0 Temperature range -40°C/+50°C		0,74						
Resistance for tensile load Characteristic resistance for concrete cone failure		M8	M10	M12	M14	M16	M20	M24
$k_{ucr,N}$		11,0						
$k_{cr,N}$		7,7						
$C_{cr,N}$		1,5 h_{ef}						
$S_{cr,N}$		3,0 h_{ef}						
Resistance for tensile load Characteristic resistance for splitting failure		M8	M10	M12	M14	M16	M20	M24
$S_{cr,sp}$ [mm]	se $h = h_{min}$	$S_{cr,sp} = 4,0 h_{ef}$						
	se $h_{min} < h < 2 h_{min}$	$S_{cr,sp} = \text{interpolated value}$						
	se $h \geq 2 h_{min}$	$S_{cr,sp} = S_{cr,Np} = 20 d (\tau_{Rk,ucr} / 7,5)^{0,5} \leq 3 h_{ef}$						
$C_{cr,sp}$ [mm]		0,5 $S_{cr,sp}$						

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601							
ESSENTIAL CHARACTERISTICS	PERFORMANCE ACCORDING TO ETA-15/0559						
Resistance for shear load Characteristic resistance for concrete pry-out failure	M8	M10	M12	M14	M16	M20	M24
k_8 [-]	2,0						
Resistance for shear load Characteristic resistance for edge failure	M8	M10	M12	M14	M16	M20	M24
l_f [mm]	$l_f = h_{ef}$ and $\leq 12 d_{nom}$						
Displacement under service load Tensile load	M8	M10	M12	M14	M16	M20	M24
$\delta_{N0,unc}$ [mm/(N/mm ²)]	0,023	0,023	0,029	0,025	0,035	0,037	0,044
$\delta_{N\infty,unc}$ [mm/(N/mm ²)]	0,056	0,056	0,061	0,061	0,073	0,077	0,081
$\delta_{0N,cr}$ [mm/(N/mm ²)]	-	0,100	0,084	0,086	0,102	-	-
$\delta_{N\infty,cr}$ [mm/(N/mm ²)]	-	0,317	0,280	0,293	0,333	-	-
Displacement under service load Shear load	M8	M10	M12	M14	M16	M20	M24
$\delta_{V0,unc}$ [mm/(N/mm ²)]	0,033	0,021	0,016	0,010	0,009	0,006	0,005
$\delta_{V\infty,unc}$ [mm/(N/mm ²)]	0,049	0,031	0,025	0,016	0,013	0,009	0,007
$\delta_{0V,cr}$ [mm/(N/mm ²)]	-	0,028	0,020	0,015	0,013	-	-
$\delta_{V\infty,cr}$ [mm/(N/mm ²)]	-	0,041	0,030	0,022	0,019	-	-

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601						
ESSENTIAL CHARACTERISTICS		PERFORMANCE ACCORDING TO ETA-15/0559				
Installation parameters		Ø8	Ø10	Ø12	Ø14	Ø16
d [mm]		8	10	12	14	16
d ₀ [mm]		12	14	16	18	20
h _i [mm]		h _{ef} + 5 mm				
h _{min} [mm]		MAX { h _{ef} + 30 mm; ≥ 100 mm; h _{ef} + 2d ₀ }				
S _{min} [mm]		50	60	65	75	80
C _{min} [mm]		40	40	40	40	50
γ _{inst} [-] Category I1		1,20				
Resistance for tensile load Characteristic steel resistance		Ø8	Ø10	Ø12	Ø14	Ø16
N _{Rk,s} [kN]		A _s x f _{uk}				
A _s [mm ²]		50	79	113	154	201
Resistance for tensile load Characteristic resistance for combined pullout and concrete cone failure		Ø8	Ø10	Ø12	Ø14	Ø16
τ _{Rk,ucr} [N/mm ²] concrete C20/25 Temperature range -40°C/+40°C (T _{mip} = 24°C)		12,0	11,0	10,0	10,0	9,0
τ _{Rk,ucr} [N/mm ²] concrete C20/25 Temperature range -40°C/+50°C (T _{mip} = 40°C)		12,0	10,0	10,0	9,5	8,5
ψ _{c,ucr} [-]		1,00				
ψ ⁰ _{sus} Temperature range -40°C/+40°C		0,68				
ψ ⁰ _{sus} Temperature range -40°C/+50°C		0,74				
Resistance for tensile load Characteristic resistance for concrete cone failure		Ø8	Ø10	Ø12	Ø14	Ø16
k _{ucr,N}		11,0				
C _{cr,N}		1,5 h _{ef}				
S _{cr,N}		3,0 h _{ef}				
Resistance for tensile load Characteristic resistance for splitting failure		Ø8	Ø10	Ø12	Ø14	Ø16
S _{cr,sp} [mm]	se h = h _{min}	S _{cr,sp} = 4,0 h _{ef}				
	se h _{min} < h < 2 h _{min}	S _{cr,sp} = interpolated value				
	se h ≥ 2 h _{min}	S _{cr,sp} = S _{cr,Np} = 20 d (τ _{Rk,ucr} / 7,5) ^{0,5} ≤ 3 h _{ef}				
C _{cr,sp} [mm]		0,5 S _{cr,sp}				
Resistance for shear load Characteristic steel resistance without lever arm		Ø8	Ø10	Ø12	Ø14	Ø16
V _{Rk,s} [kN]		0,5x A _s x f _{uk}				
k _τ		1,0				
Resistance for shear load Characteristic steel resistance with lever arm		Ø8	Ø10	Ø12	Ø14	Ø16
Characteristic bending moment M ⁰ _{Rk,s} [Nm]		1,2 x Wel x f _{uk}				
Elastic section modulus W _{el} [mm ³]		50	98	170	269	402
Resistance for shear load Characteristic resistance for concrete pry-out failure		Ø8	Ø10	Ø12	Ø14	Ø16
k ₈ [-]		2,0				
Resistance for shear load Characteristic resistance for edge failure		Ø8	Ø10	Ø12	Ø14	Ø16
l _f [mm]		l _f = h _{ef} and ≤ 12 d _{nom}				

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601					
ESSENTIAL CHARACTERISTICS	PERFORMANCE ACCORDING TO ETA-15/0559				
Displacement under service load Tensile load	Ø8	Ø10	Ø12	Ø14	Ø16
$\delta_{N0,unc}$ [mm]	0,029	0,032	0,040	0,040	0,044
$\delta_{N\infty,unc}$ [mm]	0,061	0,066	0,073	0,073	0,081
Displacement under service load Shear load	Ø8	Ø10	Ø12	Ø14	Ø16
$\delta_{0,unc/cr}$ [mm]	0,022	0,014	0,013	0,010	0,007
$\delta_{\infty,unc/cr}$ [mm]	0,033	0,021	0,020	0,014	0,011

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601 SEISMIC ASSESSMENT C1 and C2		
ESSENTIAL CHARACTERISTICS	PERFORMANCE ACCORDING TO ETA-15/0559	
Resistance for tensile load Characteristic steel resistance	M12	M16
$N_{Rk,s,C1}$ [kN]	$1,0 \times N_{Rk,s}$	
$N_{Rk,s,C2}$ [kN]	$1,0 \times N_{Rk,s}$	-
Resistance for tensile load Characteristic resistance for combined pullout and concrete cone failure	M12	M16
$\tau_{Rk,C1}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+40°C ($T_{mlp} = 24^\circ\text{C}$)	2,50	2,85
$\tau_{Rk,C1}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+50°C ($T_{mlp} = 40^\circ\text{C}$)	2,50	2,85
$\tau_{Rk,C2}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+40°C ($T_{mlp} = 24^\circ\text{C}$)	0,79	-
$\tau_{Rk,C2}$ [N/mm ²] concrete C20/25 Temperature range -40°C/+50°C ($T_{mlp} = 40^\circ\text{C}$)	0,76	-
$\Psi_{c,cr}$ [-]	1,00	
γ_{inst} [-]Category I1	1,2	
γ_{inst} [-]Category I2	1,4	
Resistance for shear load Characteristic steel resistance without level arm	M12	M16
$V_{Rk,s,C1}$ [kN]	$0,68 \times V_{Rk,s}^0$	$0,58 \times V_{Rk,s}^0$
$V_{Rk,s,C2}$ [kN]	$0,50 \times V_{Rk,s}^0$	-
Filling factor of the hole	M12	M16
α_{gap} [-]	$0,5 (1,0)^2$	

²⁾ Value in brackets valid for filled annular gap between anchor and clearance in the fixture.

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601 SEISMIC ASSESSMENT CATEGORY C2	
ESSENTIAL CHARACTERISTICS	PERFORMANCE ACCORDING TO ETA-15/0559
Displacements for tensile and shear load for seismic category C2	M12
Displacement in tensile at Damage limit state $\delta_{N,seis}$ (DLS) [mm]	0,27
Displacement in tensile at Ultimate limit state $\delta_{N,seis}$ (ULS) [mm]	0,31
Displacement in shear at Damage limit state $\delta_{V,seis}$ (DLS) [mm]	3,82
Displacement in shear at Ultimate limit state $\delta_{V,seis}$ (ULS) [mm]	6,22

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601	
ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction to fire	In the final application the thickness of the mortar layer is about 1 to 2 mm and most of the mortar is material classified class A1 according to EC Decision 96/603/EC. Therefore it may be assumed that the bonding material (synthetic mortar or a mixture of synthetic mortar and cementitious mortar) in connection with the metal anchor in the end use application do not make any contribution to fire growth or to the fully developed fire and they have no influence to the smoke hazard.

HARMONIZED TECHNICAL SPECIFICATION: EAD 330499-01-0601 E TECHNICAL REPORT TR020	
ESSENTIAL CHARACTERISTICS	PERFORMANCE
Resistance to fire	NPA

TERMINOLOGY AND SYMBOLS	
d	Diameter of anchor bolt or thread diameter
d ₀	Drill hole diameter
d _{fix}	Diameter of clearance hole in the fixture
h _{ef}	Effective anchorage depth
h ₁	Depth of the drilling hole
h _{min}	Minimum thickness of concrete member
T _{Fix}	Torque moment to installation
t _{fix}	Thickness to be fixed
S _{min}	Minimum allowable spacing
C _{min}	Minimum allowable edge distance
N _{Rk,s}	Characteristic steel- tensile resistance for static load
N _{Rk,s,C1}	Characteristic steel- tensile resistance for C1 seismic category
N _{Rk,s,C2}	Characteristic steel- tensile resistance for C2 seismic category
V _{Rk,s}	Characteristic steel- shear resistance for static load
V _{Rk,s,C1}	Characteristic steel- shear resistance for C1 seismic category
V _{Rk,s,C2}	Characteristic steel- shear resistance for C2 seismic category
τ _{Rk}	Characteristic adhesion in non-cracked concrete (uncr), cracked (cr), seismic category C1 and C2
A _s	Transversal section area
A ₅	Fracture elongation
α _{gap}	Annular gap factor
M ⁰ _{Rk,s}	Characteristic bending moment
W _{el}	Elastic section modulus
k ₇	Ductility factor
k ₈	Pryout factor
N _{Rk}	Characteristic resistance for pull-out and concrete cone for single anchor
γ _{inst}	Partial safety factors for installation
S _{cr,Np}	Spacing for ensuring the transmission of the characteristic resistance of a single anchor without spacing and edge effects in case of pullout failure
C _{cr,Np}	Edge distance for ensuring the transmission of the characteristic tensile resistance of a single anchor without spacing and edge effects in case of pullout failure
k _{uncr,N}	Un-Cracked coefficient
k _{cr,N}	Cracked coefficient
S _{cr,N}	Spacing for ensuring the transmission of the characteristic tensile resistance of a single anchor without spacing and edge effects in case of concrete cone failure
C _{cr,N}	Edge distance for ensuring the transmission of the characteristic tensile resistance of a single anchor without spacing and edge effects in case of concrete cone failure
S _{cr,sp}	Spacing for ensuring the transmission of the characteristic tensile resistance of a single anchor without spacing and edge effects in case of splitting failure
C _{cr,sp}	Edge distance for ensuring the transmission of the characteristic tensile resistance of a single anchor without spacing and edge effects in case of splitting failure
ψ _{c,ucr}	Increasing factor for un-cracked concrete
ψ _{c,cr}	Increasing factor for cracked concrete
ψ ⁰ _{sus}	Sustained load factor
l _i	Effective length
F	Service load in un-cracked (ucr) or cracked concrete (cr)
δ ₀	Short term displacement under service load in un-cracked (uncr) or cracked concrete (cr)
δ _∞	Long term displacement under service load in un-cracked (uncr) or cracked concrete (cr)
NPA	No declared performance

Regulation REACH n°1907/2006

Estimate customer,

We inform you that in the REACH supply chain our company is classified as DU: Downstream-user.

About the product detailed in the point 1 we confirm you that we don't use in our production substances classified as SVHC according to the Candidate List published on ECHA site web:

http://echa.europa.eu/chem_data/candidate_list_table_en.asp.

You can require the safety data sheet of the product to our technical department: tek@bossong.com or you can download the document from our web site www.bossong.com.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Name and function	Data and place	Sign
Andrea Taddei General Manager	Grassobbio (Bg) - Italia 28.03.2024	